



2. Type designation

NC 6- □ □ □ □

Blank: Screw-clamp connection
K: With solder "pins"
for direct connection
to printed circuit boards.

Number of contacts

10: 3N/O main contacts,
1N/O auxiliary contact

01: 3N/O main contacts.

1N/C auxiliary contact

04: 4N/O main contacts

08: 2N/O+2N/C main contacts

Rated operational current (AC-3, 380V)

Design sequence No.

Contactor

Company code

NC6 AC Contactor, 6~9A

1. General

- 1.1 Certificates: CE, UKrSEPRO, EAC, UL;
- 1.2 Electric ratings: AC50/60Hz, up to 690V, up to 9A;
- 1.3 Application: remotely makes and breaks circuit,
protect circuit from overload assembling
with proper thermal relay;
- 1.4 Utilization category: AC-1, AC-3, AC-4;
- 1.5 Ambient temperature: -5°C ~ +40°C ;
- 1.6 Altitude: ≤2000m;
- 1.7 Mounting category: III
- 1.8 Mounting conditions:
inclination between mounting plane
and vertical plane not exceed ±30°
- 1.9 Standard: IEC/EN 60947-4-1
- 1.10 IP00



3. Technical data

3.1 Contactor

★ 3P contactor AC coil operation

Items		Model	NC6-06	NC6-09
				
Rated conventional heating current(A)	AC-1		20	20
Rated operational current(A)	AC-3/AC-4	380/400V	6	9
		660/690V	3.8	5
Power of motor	kW (AC-3)	220/230V	1.5	2.2
		380/400V	2.2	4
		660/690V	3	4
	hp	240V	2	2
		400V	3	3
		600V	3	3
Operating cycles (operations/h)	Electrical	AC-3	1,200	1,200
		AC-4	300	300
	Mechanical	3,600	3,600	
Electrical life(×10 ³ operations)		AC-3	1,200	1,200
		AC-4	25	25
Mechanical life(×10 ⁶ operations)			10	10
Matching fuse model			RT16-16	RT16-20

★ 4P contactor AC operation

Items		Model	NC6-06	NC6-09
				
Rated operational current(A)	AC-1		20	20
	AC-3/AC-4	380/400V		9
		660/690V		5
Power of motor	kW (AC-3)	220V/230V/240V	1.5	2.2
		380/400V	2.2	4
		660/690V	3	4
	hp	240V	-	2
		400V	-	3
		600V	-	3
Operating cycles (operations/h)	Electrical	AC-3	1,200	1,200
		AC-4	300	300
	Mechanical		3,600	3,600
Electrical life(×10 ³ operations)		AC-3	1,200	1,200
		AC-4	25	25
Mechanical life(×10 ⁶ operations)			10	10
Matching fuse model			RT16-16	RT16-20

3.2 AC coil specifications

Items	Model	NC6-06	NC6-09
Rated control voltage (V AC)		24, 36, 48, 110, 127, 220, 230, 380, 400	
Coil power (VA)	In-rush	30	30
	Sealed	4.5	4.5

4. Terminal connection

Model	Number of piece	Conductor(mm ²)	Screw size	Tightening torque(N·m)
NC6-06	1	2.5	M3	0.5
NC6-09	1	2.5	M3	0.5

5. Accessories

5.1 Auxiliary contact

Model	Auxiliarycontact	Conventionalheating current(A)	Control capacity
	Modelof assembled contact		
NC6-06	NCF6-20;NCF6-02 NCF6-11;NCF6-40 NCF6-31;NCF6-22 NCF6-13;NCF6-04	10	AC-15:380/400V/0.95A DC-13:220/250V/0.15A
NC6-09	NCF6-20;NCF6-02 NCF6-11;NCF6-40 NCF6-31;NCF6-22 NCF6-13;NCF6-04	10	AC-15:380/400V/0.95A DC-13:220/250V/0.15A

5.2 Assembly with thermal over-load relay

Model of contactor	Assembled thermal over-load relay			
	Model	Rated current(A)	Recommended fuse type	
			aM	gG
 NC6-09	 NC6-11.5	0.1~0.16	0.25	2
		0.16~0.25	0.5	2
		0.25~0.4	1	2
		0.4~0.63	1	2
		0.63~1	2	4
		1~1.6	2	4
		1.25~2	4	6
		1.6~2.5	4	6
		2.5~4	6	10
		4~6	8	16
		5.5~8	12	20
		7~10	12	20
		9~13	16	25

6. Overall and mounting dimensions (mm)

